Printing date 20.03.2018 Version number 11 Revision: 20.03.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: RADEX 110 ML
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Anticorrosion additive
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: RADEX-Europe LTD

Uriekstes iela 3, Riga, Latvija, LV-1005 Tel.: +37167387778

Tel.: +37167387778 FAX: +37167387789 info@radex-europe.lv

- · Further information obtainable from: Product safety Department
- **1.4 Emergency telephone number:** Tel: +37167387778

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.



GHS09

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

STOT SE 3

H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS02 GHS07

7 GHS08

S08 GHS09

- · Signal word Danger
- · Hazard-determining components of labelling: Naphtha (petroleum), hydrodesulfurized heavy Naphtha (petroleum), hydrotreated heavy

(Contd. on page 2)

Printing date 20.03.2018 Version number 11 Revision: 20.03.2018

Trade name: RADEX 110 ML

(Contd. of page 1)

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H372 Causes damage to the central nervous system through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P243 Take precautionary measures against static discharge.
 P280 Wear protective gloves/protective clothing/eye protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains Calcium Sulfonate. May produce an allergic reaction.

· 2.3 Other hazards

The petroleum naphtha / petroleum distillate / lubricating oil meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with additions.

· Dangerous components:		
CAS: 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	25-<50%
EC number: 919-446-0	♠ Flam. Liq. 3, H226; ♦ STOT RE 1, H372; Asp. Tox. 1, H304;	
Reg.nr.: 01-2119458049-33	♦ Aquatic Chronic 2, H411; ♦ STOT SE 3, H336	
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	5-<10%
EC number: 919-857-5	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336	
Reg.nr.: 01-2119463258-33		
CAS: 61789-86-4	Calcium Sulfonate	5-<10%
	♦ Skin Sens. 1B, H317	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air or oxygen; call for doctor.
- · After skin contact: If skin irritation continues, consult a doctor.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

Disorientation

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

(Contd. on page 3)

Printing date 20.03.2018 Version number 11 Revision: 20.03.2018

Trade name: RADEX 110 ML

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin, eyes and clothes.

· 6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Use only in well ventilated areas.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- \cdot 7.3 *Specific end use*(s) *No further relevant information available.*

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

(Contd. on page 4)

Printing date 20.03.2018 Version number 11 Revision: 20.03.2018

Trade name: RADEX 110 ML

(Contd. of page 3)

· DNELs		
CAS: 6474	12-82-1 Naphtha (petroleum), hydrodesulfurized i	heavy
Oral	Long-term - systemic effects, general population	26 mg/kg bw/day (General Population)
Dermal	Long-term - systemic effects, worker	44 mg/kg bw/day (Worker)
	Long-term - systemic effects, general population	26 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, worker	330 mg/m3 (Worker)
	Long-term - systemic effects, general population	71 mg/m3 (General Population)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.



Filter A

· Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber

Recommended thickness of the material: ≥ 0.12 mm

· Penetration time of glove material

< 480 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Use protective suit.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: Beige
Odour: Characteristic

(Contd. on page 5)

Printing date 20.03.2018 Version number 11 Revision: 20.03.2018

Trade name: RADEX 110 ML

	(Contd. of page
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition Melting point/freezing point: Initial boiling point and boiling range.	Undetermined. : 145 °C
· Flash point:	>30 °C (DIN 53213)
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	>200 °C
Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
· Explosion limits: Lower: Upper:	0.6 Vol % 7 Vol %
· Vapour pressure At 20 °C: · Vapour pressure At 50 °C:	27 hPa 15 hPa
· Density At 20 °C: · Relative density · Vapour density · Evaporation rate	0.85 g/cm³ (DIN 51757) Not determined. Not determined. Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic At 20 °C:	Not determined. 30 s (DIN 53211/4)
· Solvent content: Organic solvents:	52.8 %
Solids content: • 9.2 Other information • VOC (EU): • VOC (EU): • VOCV:	48.5 % (DIN 53216) No further relevant information available. 52.79 % 448.7 g/l 52.79 %

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

Printing date 20.03.2018 Version number 11 Revision: 20.03.2018

Trade name: RADEX 110 ML

(Contd. of page 5)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values re	elevant fo	or classification:	

CAS: 64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy

Oral LD50 >5,000 mg/kg (RAT)
Dermal LD50 3,400 mg/kg (RABBIT)

CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy

 Oral
 LD50
 >5,000 mg/kg (RAT)

 Dermal
 LD50
 >3,000 mg/kg (RAT)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information: No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure

Causes damage to the central nervous system through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

CAS: 64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy

EC50/48 h 10-22 mg/l (DAPHNIA MAGNA)

EC50/72 h 4.6-10 mg/l (ALGAE)

EC50/96 h 10-30 mg/L (Fish)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

GB

Printing date 20.03.2018 Version number 11 Revision: 20.03.2018

Trade name: RADEX 110 ML

(Contd. of page 6)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Dispose of as dangerous waste.

· European waste catalogue	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP 3	Flammable
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 14	Ecotoxic

- · Uncleaned packaging:
- \cdot **Recommendation:** Disposal must be made according to official regulations.

· 14.1 UN-Number · ADR/RID/ADN, IMDG, IATA	UN1139
14.2 UN proper shipping name ADR/RID/ADN	1139 COATING SOLUTION, ENVIRONMENTAL HAZARDOUS
· IMDG · IATA	COATING SOLUTION (TURPENTINE SUBSTITUTE MARINE POLLUTANT COATING SOLUTION
	COATING SOLUTION
14.3 Transport hazard class(es) ADR/RID/ADN, IMDG	
Class	3 Flammable liquids.
Label	3
Class Label	3 Flammable liquids.
14.4 Packing group	
ADR/RID/ADN, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substanc Naphtha (petroleum), hydrodesulfurized heavy
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR/RID/ADN):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler): EMS Number:	30 <u>F</u> -E,S-E

Printing date 20.03.2018 Version number 11 Revision: 20.03.2018

Trade name: RADEX 110 ML

	(Contd. of page
Stowage Category	A
14.7 Transport in bulk according to Anne	x II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	Tansport classification ADR/IMGD is based on packaging
	>30 $ltr(IMDG)$, $<$ 450 $ltr(ADR)$.
	For other packaging untis different classification can
	apply.
ADR/RID/ADN	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
· · · · · · · · ·	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1139 COATING SOLUTION, 3, II.
	ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms









GHS02

GHS07

GHS08

GHS09

· Signal word Danger

· Hazard-determining components of labelling:

Naphtha (petroleum), hydrodesulfurized heavy Naphtha (petroleum), hydrotreated heavy

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H372 Causes damage to the central nervous system through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P243 Take precautionary measures against static discharge.
P280 Wear protective gloves/protective clothing/eye protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

(Contd. on page 9)

Printing date 20.03.2018 Version number 11 Revision: 20.03.2018

Trade name: RADEX 110 ML

(Contd. of page 8)

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	52.8

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H372 Causes damage to the central nervous system through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

- · Department issuing SDS: Product safety department.
- · Contact: info@radex-europe.lv
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

 ${\it Skin Sens. 1B: Skin sensitisation-Category 1B}$

 $STOT\,SE\,3\colon Specific\ target\ organ\ toxicity\ (single\ exposure)-Category\ 3$

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

 $A quatic\ Chronic\ 2:\ Hazardous\ to\ the\ aquatic\ environment\ -\ long\ -term\ aquatic\ hazard\ -\ Category\ 2$

* Data compared to the previous version altered.