Printing date 11.02.2019 Version number 17 Revision: 11.02.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: <u>RADEXSEAL BS</u>

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Sealant

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

RADEX-Europe LTD Uriekstes iela 3, Riga, Latvija, LV-1005 Tel: +37167387778

Tel.: +37167387778 FAX: +37167387789 info@radex-europe.lv

- · Further information obtainable from: Product safety Department
- **1.4 Emergency telephone number:** *Tel:* +37167387778

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

02 GHS07

GHS08

- · Signal word Warning
- · Hazard-determining components of labelling:

Xylene, mixed isomers, pure

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

(Contd. on page 2)

Printing date 11.02.2019 Version number 17 Revision: 11.02.2019

Trade name: RADEXSEAL BS

(Contd. of page 1)

25-<50%

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P243 Take precautionary measures against static discharge.
 P280 Wear protective gloves/protective clothing/eye protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· **PBT**: Not applicable. · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with additions.

· Dangerous components:

CAS: 1330-20-7

EINECS: 215-535-7

Reg.nr.: 01-2119488216-32

Xylene, mixed isomers, pure

Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304;
Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye

Irrit. 2, H319; STOT SE 3, H335

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Immediately rinse with water.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Sand. Do not use water.

CO2, sand, extinguishing powder. Do not use water.

(Contd. on page 3)

Printing date 11.02.2019 Version number 17 Revision: 11.02.2019

Trade name: RADEXSEAL BS

(Contd. of page 2)

· For safety reasons unsuitable extinguishing agents:

Water

Water with full jet

· 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin, eyes and clothes.

· 6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Use only in well ventilated areas.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 1330-20-7 Xylene, mixed isomers, pure

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

(Contd. on page 4)

Version number 17 Printing date 11.02.2019 Revision: 11.02.2019

Trade name: RADEXSEAL BS

(Contd. of page 3)

· Regulatory information WEL: EH40/2018

· DNELs			
CAS: 1330-20-7 Xylene, mixed isomers, pure			
Oral	Long-term - systemic effects, general population	12.5 mg/kg bw/day (General Population)	
Dermal	Long-term - systemic effects, worker	212 mg/kg bw/day (Worker)	
	Long-term - systemic effects, general population	125 mg/kg bw/day (General population)	
Inhalative	Acute - Local effects, worker	442 mg/m3 (Worker)	
	Long-term - systemic effects, worker	221 mg/m3 (Worker)	
	Long-term - local effects, worker	221 mg/m3 (Worker)	
	Acute - systemic effects, general population	260 mg/m3 (General Population)	
	Acute - systemic effects, worker	442 mg/m3 (Worker)	
	Acute - local effects, general population	260 mg/m3 (General Population)	
	Long-term - systemic effects, general population	65.3 mg/m3 (General Population)	

· PNECs

CAS: 1330-20-7 Xylene, mixed isomers, pure

Long-term - local effects, general population

Cits: 1000 20 7 Hytelic, mateursomers, pure	
Aquatic compartment - freshwater	0.327 mg/L (not specified)
Aquatic compartment - marine water	0.327 mg/L (not specified)
Aquatic compartment - sediment in freshwater	12.46 mg/kg sed dw (not specified)
Aquatic compartment - sediment in marine water	12.46 mg/kg sed dw (not specified)
Terrestrial compartment - soil	2.31 mg/kg dw (not specified)
Sewage treatment plant	6.58 mg/L (not specified)

65.3 mg/m3 (General Population)

· Ingredients with biological limit values:

CAS: 1330-20-7 Xylene, mixed isomers, pure

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Regulatory information BMGV: EH40/2011
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Respiratory protection:



Filter A

· Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the (Contd. on page 5)

Printing date 11.02.2019 Version number 17 Revision: 11.02.2019

Trade name: RADEXSEAL BS

(Contd. of page 4)

application.

Fluorocarbon rubber (Viton)

Recommended thickness of the material: ≥ 0.12 mm

· Penetration time of glove material

> 480 min.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Use protective suit.

9.1 Information on basic physical and General Information	chemical properties
· General Information · Appearance:	
Form:	Pasty
Colour:	Grey
· Odour:	Characteristic
· Odour threshold:	Not determined.
pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling rang	e: 136-145 °C
· Flash point:	23-29 °C (DIN 53213)
Flammability (solid, gas):	Not applicable.
· Ignition temperature:	500 °C
Decomposition temperature:	Not determined.
\cdot $Auto-ignition temperature:$	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive ai vapour mixtures are possible.
· Explosion limits:	
Lower:	1 Vol %
Upper:	7.1 Vol %
· Vapour pressure At 20 °C:	10 hPa
· Vapour pressure At 50 °C:	20 hPa
Density At 20 °C:	1.22 g/cm³ (DIN 51757)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.

Printing date 11.02.2019 Version number 17 Revision: 11.02.2019

Trade name: RADEXSEAL BS

	(Contd. of page 1)	age 5
· Solvent content:		
Organic solvents:	32.7 %	
Solids content:	66.0 % (DIN 53216)	
9.2 Other information	No further relevant information available.	
· <i>VOC (EU):</i>	32.68 %	
<i>VOC (EU):</i>	398.7 g/l	
VOCV:	32.68 %	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

CAS: 1330-20-7 Xylene, mixed isomers, pure

Oral	LD50	3,523-4,000 mg/kg (RAT)
Dermal	LD50	12,126 mg/kg (RABBIT)
Inhalative	LC50/4 h	6,350 mg/l (RAT)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information: No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)

Printing date 11.02.2019 Version number 17 Revision: 11.02.2019

Trade name: RADEXSEAL BS

(Contd. of page 6)

- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Dispose of as dangerous waste.

· European waste catalogue		
08 01 11*	11* waste paint and varnish containing organic solvents or other hazardous substances	
HP 3	Flammable	
HP 4	Irritant - skin irritation and eye damage	
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP 6	Acute Toxicity	

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number		
ADR/RID/ADN, ADN	Void	
ADWKID/ADW, ADW	Void according to 2.2.3.1.5	
IMDG, IATA	UN1263	
14.2 UN proper shipping name		
ADR/RID/ADN, ADN	Void	
IMDG, IATA	PAINT	
·	1711111	
14.3 Transport hazard class(es)		
ADR/RID/ADN, ADN		
Class	Void	
IMDG, IATA		
8		
Class	3 Flammable liquids.	
Label	3	
14.4 Packing group		
ADR/RID/ADN	Void	
IMDG, IATA	III	
14.5 Environmental hazards:		
14.5 Environmental hazards: Marine pollutant:	No	

Version number 17 Printing date 11.02.2019 Revision: 11.02.2019

Trade name: RADEXSEAL BS

	(Contd. of page
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	A
· 14.7 Transport in bulk according to Anne	x II of
Marpol and the IBC Code	Not applicable.
$\cdot \textit{Transport/Additional information:}$	Tansport classification ADR/IMGD is based on packaging >30ltr(IMDG), <450ltr(ADR). For other packaging untis different classification can
	apply.
· ADR/RID/ADN	
· Remarks:	Transport is in line with the remarks under 2.2.3.1.5 of th ADR code till a volume of 450 ltr. If ADR > 450 ltr that class 3, packaging group III must be applied with accessory UN-number.
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Remarks:	Transport is in line with the remarks under 2.3.2.5 of th
	IMDG code till a volume of 30 ltr. If $IMDG > 30$ ltr than
	class 3, packaging group III must be applied.
· UN ''Model Regulation'':	Void

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07 GHS08

- · Signal word Warning
- · Hazard-determining components of labelling:

Xylene, mixed isomers, pure

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210

P243 Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 9)

Printing date 11.02.2019 Version number 17 Revision: 11.02.2019

Trade name: RADEXSEAL BS

(Contd. of page 8)

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	32.7

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

- · Department issuing SDS: Product safety department.
- · Contact: info@radex-europe.lv
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

 $DNEL: \ Derived \ No-Effect \ Level \ (REACH)$

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

* * Data compared to the previous version altered.